







》 FR Series Float less Level Relay

| | | | | |
|-----------------------|--|--|---|---|
| Outline | 40×50mm (under panel type) May select and purchase Y-40 to transform for the plate form Fixed Hole 43×53mm | | | |
| Type | Standard | Long Distance | High Sensitivity | Two Wires |
| Model | FR-1-□□□V | FR-1L-□□□V | FR-1H-□□□V | FR-2-□□□V |
| Figure |  |  |  |  |
| ON Resistance | <30KΩ | <4KΩ | <70KΩ | <30KΩ |
| OFF Resistance | >60KΩ | >15KΩ | >300KΩ | >60KΩ |
| Length of Cable | <1000M | <4000M | <50M | <800M |
| Power Supply | 110V or 220V or 380VAC±20% 50/60Hz | | | |
| Electrode Consumption | 14VAC | | | |
| Response Time | ON<80ms、OFF<160ms | | | |
| Dielectric Strength | 2.5KV/1min. | | | |
| Circumstance | -20℃~+80℃ ; 35%~85%RH | | | |

》 PR Series Voltage & Phase Relay

| | | |
|---------------------|--|---|
| Outline | 40×50mm (under panel type) May select and purchase Y-40 to transform for the plate form Fixed Hole 43×53mm | |
| Product | Phase & Voltage Relay | Phase Relay |
| Model | PVR-3-□□□V | PR-1-□□□V |
| Figure |  |  |
| Power Supply | 230VAC or 380VAC or 440VAC or 480VAC 50/60Hz | |
| High Voltage Limit | ±20% | |
| Low Voltage Limit | ±20% | |
| ON Delay Time | 1.0~10.0 Sec Adjustable | |
| Reset Delay Time | 1.0~10.0 Sec Adjustable | 2 Sec (Fixed) |
| Output Status | Normal ON Relay (RUN) | |
| Dielectric Strength | 2.5KV/1min. | |
| Circumstance | -20℃~+80℃ ; 35%~85%RH | |